HONDO K24 REBEL SERIES



- 3D milling on piston crowns for ready to install finish
- Side gas ports for better ring seal
- Ratios figured for 90mm x .030 head gasket @ 9.120" Deck Height
- Top ring down dimension: .300"
 Designed for pin buttons for maximum strength
- Premium H-13 .200W wrist pins included

- Premium 1.2mm x 1.2mm x 2.8mm ring package included

 Oversized valve pockets for larger than stock valve sizes

 Valve pocket depth: 0.200" intake and 0.150" exhaust

 2618 material for High HP/Boost applications rated for 1400hp

∫ K	K20/K24 Block: 86.0mm Std Bore 86.0mm Std Stroke						COMPRESSION RATIO			
Bore	Stroke	Rod	C.D.	Weight	Pin	CC's	50CC	Ring Set	Part #	
87.0m	m 99.0mm	5.984	1.181	call	.866 x 2.250	-6.0cc	10.1	09583425	71200	
87.5m	m 99.0mm	5.984	1.181	call	.866 x 2.250	-6.0cc	10.2	09583445	71201	
88.0m	m 99.0mm	5.984	1.181	call	.866 x 2.250	-6.0cc	10.3	09583465	71202	
89.0m	m 99.0mm	5.984	1.181	call	.866 x 2.250	-6.0cc	10.4	09583505	71203	

Optional H-13, M2 and TP-1 wrist pins available as a upgrade to any piston part number. Contact Diamond Pistons for tech assistance.



DiamondRacing.net Tech support 586.792.6620

